

NATIONAL REFINERY LIMITED

7-B, Korangi Industrial Zone, Korangi, Karachi-74900, (Pakistan) P.O.Box No. 8228 Telephone: 35064981-3 PABX Fax: 92-21-35054663Direct:35121836 smgr_procurement@nrlpak.com

Request For Quotation

Tel: Fax:

Vendor No. 200861

Page 1 of 2.

Our Ref No.28269

No. 6100021793 Dated 14.02.2024 Due Date: 14.03.2024

Shipment to Karachi Via: Air / Sea

Shipment to Karachi By:

Managar Imparta

Manager Imports

Please send us your best offer in the form of Performa Invoice on your letterhead based on C&F Karachi and at least provide the gross weight & dimensions along with complete address of Ex-works/ FOB destination, duly signed, for the under mentioned items. In case of local agents / representative original Invoice from the Principal must be enclosed. Quotation should be submitted along with our attached "BID FORM" completely filled in.

Incomplete and conditional offers will not be entertained. No advance payment will be made. All bank charges inside Pakistan will be on our account and all bank charges outside Pakistan will be on beneficiary's account. The bids are to be submitted in the sealed envelope clearly marked as Manager Imports and our reference No. mentioned above and courier/ e-mail to us. Please e-mail/ fax us your courier Slip No. The bids to be reached latest by the above mentioned date.

Material	Description	Unit	Quantity	Unit Price	Freight/ Packing Charges	Total C&F Value (Currency)
26-027-105	POUR POINT DEPRESSANT FOR FURNACE OIL.	DM	240			
	SPECIFICATION OF PPD FOR NRLâ€#s F.OIL Reduced crude from Arab Light (Paraffinic nature) and reduced crude from local crude oil (Naphthenic nature) are the main components of NRLâ€#s F.oil pool. The pour point of NRLâ€#s F.oil, is about +40C. The objective of PPD is to depress pour point of NRLâ€#s F.oil from +39C to +18C. Effectiveness of PPD in NRLâ€#s F.oil should be maintained and not vary with time. Spec / physical parameters of required PPD. 1. Flash point, C (ASTM, D-93) (>40 PPD. 2. Viscosity @ 40C, cSt (ASTM, D-445) (<200) 3. PPD's Pour Point (ASTM D97) +18C to +21C 4. Solubility. (Be soluble in NRLâ€#s F.oil) 5. Shelf life of offered PPD. (2 years, minimum) at date of receipt at NRL 6. Specification of quoted PPD. (To be	DIVI	240			
	26-027-105	POUR POINT DEPRESSANT FOR FURNACE OIL. SPECIFICATION OF PPD FOR NRLâ€#s F.OIL Reduced crude from Arab Light (Paraffinic nature) and reduced crude from local crude oil (Naphthenic nature) are the main components of NRLâ€#s F.oil pool. The pour point of NRLâ€#s F.oil, is about +40C. The objective of PPD is to depress pour point of NRLâ€#s F.oil from +39C to +18C. Effectiveness of PPD in NRLâ€#s F.oil should be maintained and not vary with time. Spec / physical parameters of required PPD. 1. Flash point, C (ASTM, D-93) (>40) 2. Viscosity @ 40C, cSt (ASTM, D-445) (<200) 3. PPD's Pour Point (ASTM D97) +18C to +21C 4. Solubility. (Be soluble in NRLâ€#s F.oil) 5. Shelf life of offered PPD. (2 years, minimum) at date of receipt at NRL 6. Specification of quoted PPD. (To be provided by vender with quotation) 7. MSDS of offered PPD. (To be	POUR POINT DEPRESSANT FOR FURNACE OIL. SPECIFICATION OF PPD FOR NRLâ€#s F.OIL Reduced crude from Arab Light (Paraffinic nature) and reduced crude from local crude oil (Naphthenic nature) are the main components of NRLâ€#s F.oil pool. The pour point of NRLâ€#s F.oil, is about +40C. The objective of PPD is to depress pour point of NRLâ€#s F.oil from +39C to +18C. Effectiveness of PPD in NRLâ€#s F.oil should be maintained and not vary with time. Spec / physical parameters of required PPD. 1. Flash point, C (ASTM, D-93) (>40) 2. Viscosity @ 40C, CSt (ASTM, D-445) (<200) 3. PPD's Pour Point (ASTM D97) +18C to +21C 4. Solubility. (Be soluble in NRLâ€#s F.oil) 5. Shelf life of offered PPD. (2 years, minimum) at date of receipt at NRL 6. Specification of quoted PPD. (To be provided by vender with quotation) 7. MSDS of offered PPD. (To be provided by vender with quotation)	POUR POINT DEPRESSANT FOR FURNACE OIL. SPECIFICATION OF PPD FOR NRLâ€#s F.OIL Reduced crude from Arab Light (Paraffinic nature) and reduced crude from local crude oil (Naphthenic nature) are the main components of NRLâ€#s F.oil pool. The pour point of NRLâ€#s F.oil, is about +40C. The objective of PPD is to depress pour point of NRLâ€#s F.oil from +39C to +18C. Effectiveness of PPD in NRLâ€#s F.oil should be maintained and not vary with time. Spec / physical parameters of required ppD. 1. Flash point, C (ASTM, D-93) (>40) 2. Viscosity @ 40C, cSt (ASTM, D-445) (<200) 3. PPD's Pour Point (ASTM D97) +18C to +21C 4. Solubility. (Be soluble in NRLâ€#s F.oil) 5. Shelf life of offered PPD. (2 years, minimum) at date of receipt at NRL 6. Specification of quoted PPD. (To be provided by vender with quotation) 7. MSDS of offered PPD. (To be provided by vender with quotation)	Price 26-027-105 POUR POINT DEPRESSANT FOR FURNACE OIL. SPECIFICATION OF PPD FOR NRLâ€#\$ F.OIL Reduced crude from Arab Light (Paraffinic nature) and reduced crude from local crude oil (Naphthenic nature) are the main components of NRLâ€#\$ F.oil pool. The pour point of NRLâ€#\$ F.oil, is about +40C. The objective of PPD is to depress pour point of NRLâ€#\$ F.oil from +39C to +18C. Effectiveness of PPD in NRLâ€#\$ F.oil should be maintained and not vary with time. Spec / physical parameters of required PPD. 1. Flash point, C (ASTM, D-93) (>40) 2. Viscosity @ 40C, cSt (ASTM, D-445) (<200) 3. PPD's Pour Point (ASTM D97) +18C to +21C 4. Solubility. (Be soluble in NRLâ€#\$ F.oil) 5. Shelf life of offered PPD. (2 years, minimum) at date of receipt at NRL 6. Specification of quoted PPD. (To be provided by vender with quotation) 7. MSDS of offered PPD. (To be provided by vender with quotation)	Material Description Unit Quantity Unit Price Packing Charges 26-027-105 POUR POINT DEPRESSANT FOR FURNACE OIL. SPECIFICATION OF PPD FOR NRLâc#s F.OIL Reduced crude from Arab Light (Paraffinic nature) and reduced crude from local crude oil (Naphthenic nature) are the main components of NRLâc#s F.oil pool. The pour point of NRLâc#s F.oil, is about +40C. The objective of PPD is to depress pour point of NRLâc#s F.oil should be maintained and not vary with time. Spec / physical parameters of required PPD. 1. Flash point, C (ASTM, D-93) (>40) 2. Viscosity @ 40C, cSt (ASTM, D-445) (<200) 3. PPD's Pour Point (ASTM D97) +18C to +21C 4. Solubility. (Be soluble in NRLâc#s F.oil) 5. Shelf life of offered PPD. (2 years, minimum) at date of receipt at NRL 6. Specification of quoted PPD. (To be provided by vender with quotation) 7. MSDS of offered PPD. (To be provided by vender with quotation)

YOUR REF. NO.

DATE: AUTHORIZED SIGNATURE



NATIONAL REFINERY LIMITED

7-B, Korangi Industrial Zone, Korangi, Karachi-74900, (Pakistan) P.O.Box No. 8228 Telephone: 35064981-3 PABX Fax: 92-21-35054663Direct:35121836 smgr_procurement@nrlpak.com

Request For Quotation

Tel: Fax:

Vendor No. 200861

Page 2 of 2.

Our Ref No. 28269

No. <u>6100021795</u> Dated <u>14.02.2024</u> Due Date: <u>14.03.2024</u>

Shipment to Karachi Via: Air / Sea

Shipment to Karachi By:

Item	Material	Description	Unit	Quantity	Unit Price	Freight/ Packing Charges	Total C&F Value (Currency)
		required to maintain the fluidity of PPD					