



NATIONAL REFINERY LIMITED

7-B, Korangi Industrial Zone, Korangi, Karachi-74900, (Pakistan)
P.O.Box No. 8228
Telephone: 35064981-3 PABX Fax: 92-21-35054663 Direct: 35121836
smgr_procurement@nrlpak.com

Request For Quotation

Page 1 of 3.

Tel :
Fax :
Vendor No. 200861

Our Ref No. WHF-4016

No. 6100022321
Dated 15.05.2024

Due Date: 30.05.2024

Shipment to Karachi Via: Air / Sea

Shipment to Karachi By : _____

Manager Imports

Please send us your best offer in the form of Performa Invoice on your letterhead based on C&F Karachi and at least provide the gross weight & dimensions along with complete address of Ex-works/ FOB destination, duly signed, for the under mentioned items. In case of local agents / representative original Invoice from the Principal must be enclosed. Quotation should be submitted along with our attached "BID FORM" completely filled in.

Incomplete and conditional offers will not be entertained. No advance payment will be made. All bank charges inside Pakistan will be on our account and all bank charges outside Pakistan will be on beneficiary's account. The bids are to be submitted in the sealed envelope clearly marked as Manager Imports and our reference No. mentioned above and courier/ e-mail to us. Please e-mail/ fax us your courier Slip No. The bids to be reached latest by the above mentioned date.

Item	Material	Description	Unit	Quantity	Unit Price	Freight/ Packing Charges	Total C&F Value (Currency)
00010	06-327-006K1	GASKET SHEET : 2 m X 1.5 m X 1.5 mm THK. KLINGERITE 1000 MATERIAL: GRAPHITE CORE REINFORCED WITH SS 316-L WIRE MESH *SURFACE: COATED WITH ANTI STICK COATING TO FACILITATE GASKET REPLACEMENT WITHOUT DAMAGING FLANGE FACING SPECIFICATION AS PER ASTM-F-36A MAX. WORKING PRESSURE : 200 BAR MAX. WORKING TEMPERATURE : 550°C COMPRESSIBILITY : 15-35% DENSITY : 1-1.3gm/cm3 PH : 0-14 *CUTTING AND HANDLING: GOOD SHEARING PROPERTIES FOR GASKET CUTTING GASKET CORE, MESH AND SURFACE SHOULD BE ADEQUATELY BONDED FOR SAFE HANDLING * LITRETURE/CATALOGUE OF QUOTED GASKET SHEETS ALONG WITH MSDS (material safety data sheet) TO BE PROVIDED WITH QUOTATIONS. *SERVICE: THE GASKET SHOULD BE APPLICABLE FOR A WIDE RANGE OF MEDIA i.e. HYDROCARBON, WATER AND STEAM etc. EVEN IN STRONG OXIDATION ENVIRONMENT AT HIGH TEMPERATURE AND PRESSURE	SHT	30			

YOUR REF. NO.

DATE:

AUTHORIZED SIGNATURE



NATIONAL REFINERY LIMITED

7-B, Korangi Industrial Zone, Korangi, Karachi-74900, (Pakistan)
P.O.Box No. 8228
Telephone: 35064981-3 PABX Fax: 92-21-35054663 Direct: 35121836
smgr_procurement@nrlpak.com

Request For Quotation

Page 2 of 3.

Tel :
Fax :
Vendor No. 200861

Our Ref No. WHF-4016

No. 6100022321

Dated 15.05.2024

Due Date: 30.05.2024

Shipment to Karachi Via: Air / Sea

Shipment to Karachi By : _____

Item	Material	Description	Unit	Quantity	Unit Price	Freight/ Packing Charges	Total C&F Value (Currency)
00020	06-327-009K1	<p>GASKET SHEET : 2 m X 1.5 m X 3 mm THK.</p> <p>GRAPHITE SHEET REINFORCED WITH S.S-316L WIRE MESH AS PER ASTM-F-36A MAX.WORKING PRESSURE: 200 BAR MAX.WORKING TEMPERATURE: 550°C COMPRESSIBILITY: 15 - 35% DENSITY: 1 - 1.3 gm/cm3 pH: 0 - 14 ANTI STOCK LAYER ON BOTH SIDES OF GASKET SHEET. SERVICE: THE GASKET SHOULD BE APPLICABLE FOR A WIDE RANGE OF MEDIA i.e. HYDRO CARBON, WATER AND STEAM etc. EVEN IN THE STRONG OXIDATION ENVIRONMENT AT HIGH TEMPERATURE AND PRESSURE. *CUTTING AND HANDLING: GOOD SHEARING PROPERTIES FOR GASKET CUTTING GASKET CORE, MESH AND SURFACE SHOULD BE ADEQUATELY BONDED FOR SAFE HANDLING * LITRETURE/CATALOGUE OF QUOTED GASKET SHEETS ALONG WITH MSDS (material safety data sheet) TO BE PROVIDED WITH QUOTATIONS.</p>	SHT	95			



NATIONAL REFINERY LIMITED

7-B, Korangi Industrial Zone, Korangi, Karachi-74900, (Pakistan)
P.O.Box No. 8228
Telephone: 35064981-3 PABX Fax: 92-21-35054663 Direct: 35121836
smgr_procurement@nrlpak.com

Request For Quotation

Page 3 of 3.

Tel :
Fax :
Vendor No. 200861

Our Ref No. WHF-4016

No. 6100022321
Dated 15.05.2024

Due Date: 30.05.2024

Shipment to Karachi Via: Air / Sea

Shipment to Karachi By : _____

Item	Material	Description	Unit	Quantity	Unit Price	Freight/ Packing Charges	Total C&F Value (Currency)
00030	06-327-003K1	<p>GASKET SHEET : 2 m X 1.5 m X 0.8 mm THK.</p> <p>KLINGERITE 1000 MATERIAL: GRAPHITE CORE REINFORCED WITH SS 316-L WIRE MESH *SURFACE: COATED WITH ANTI STICK COATING TO FACILITATE GASKET REPLACEMENT WITHOUT DAMAGING FLANGE FACING</p> <p>SPECIFICATION AS PER ASTM-F-36A MAX. WORKING PRESSURE : 200 BAR MAX. WORKING TEMPERATURE : 550°C COMPRESSIBILITY : 15-35% DENSITY : 1-1.3gm/cm3 PH : 0-14 *CUTTING AND HANDLING: GOOD SHEARING PROPERTIES FOR GASKET CUTTING GASKET CORE, MESH AND SURFACE SHOULD BE ADEQUATELY BONDED FOR SAFE HANDLING * LITRETURE/CATALOGUE OF QUOTED GASKET SHEETS ALONG WITH MSDS (material safety data sheet) TO BE PROVIDED WITH QUOTATIONS.</p> <p>*SERVICE: THE GASKET SHOULD BE APPLICABLE FOR A WIDE RANGE OF MEDIA i.e. HYDROCARBON, WATER AND STEAM etc. EVEN IN STRONG OXIDATION ENVIRONMENT AT HIGH TEMPERATURE AND PRESSURE</p>	SHT	5			