



NATIONAL REFINERY LIMITED

7-B, Korangi Industrial Zone, Korangi, Karachi-74900, (Pakistan)
P.O.Box No. 8228
PABX: 5064981-86 Dir. 5060842 Fax No. (92-21) 5054679 & 5054663

NRL-FAF-LRU-001
Rev.: # 00
Dt.: 28-07-2003

Request For Quotation

Tel :
Fax :
Vendor No. 102518

Our Ref No. WHL-8020

No. 6000148675
Dated 30.10.2023

Please return this form duly completed and signed by authorized person in the sealed envelope. The due date for submission of tenders is

Due Date: 09.11.2023

Last time for submission (1:30 pm)

PLEASE DROP YOUR QUOTATION IN BOX NO. 1

[Signature]
MANAGER LOCAL PURCHASE

Please quote your lowest prices for the following items. Your offer should remain valid for 45 DAYS. Please drop your quotation in above mentioned Box No. kept at NRL Reception Office. Please quote your GST No. and mention prices are inclusive or exclusive of GST. If not it will be assumed to be inclusive.

Delivery: Free delivery at our Ware House Collect Ex-Your Shop/Premises
Requirement: Within 7 days of our Purchase Order Immediate

Item	Material	Description	Unit	Quantity	Unit Pr.	Sales Tax	Total Amount Inclusive GST
00010	39-130-001A1	<p>WALK THROUGH GATE (BRANDED) AMERICAN OR EUROPEAN IP-65 OR IP-66 STANDARD UNIT. 02-YEARS WARRANTY REQUIRED THROUGH AUTHORIZED DISTRIBUTOR DEMO ALSO REQUIRED PREFERABLY LATEST MODEL OF AMERICAN ORIGINAL WALK THOROUGH GATE. IP-65 OR IP-66 STANDARD (REQUIRED) (AS PER ATTACHED SPECIFICATIONS)</p> <p>NOTE : 1. BID SHALL BE OPENED ON DUE DATE AS MENTIONED ABOVE AT LEAST THIRTY MINUTES AFTER DEADLINE FOR SUBMISSION OF BID. 2. BIDS SHALL BE OPENED PUBLICLY IN THE PRESENCE OF THE BIDDERS OR THEIR REPRESENTATIVE WHO MAY CHOOSE TO ATTEND. 3. PLEASE QUOTE PRICES ACCORDING TO OUR SPECIFICATION PREFERABLY ON OUR REQUEST FOR QUOTATION, HOWEVER OFFER ON THE SUPPLIER'S OWN FORMATE/LETTER HEAD WILL ALSO BE ACCEPTABLE. 4. CUTTING/ALTERATION IN THE RFQ MUST BE AVOIDED AS FAR AS POSSIBLE. HOWEVER IN CASE CUTTING/ALTERATION IS INEVITABLE, THE SAME MAYBE CARRIED OUT WITH PROPER SIGNATURE/STAMP OF THE SUPPLIER. 5. IF YOU DO NOT MENTION G.S.T IN YOUR QUOTATION, IT WILL BE ASSUMED TO BE INCLUSIVE. 6. PLEASE MENTION YOUR NTN & GST NO. AS WELL AS OUR GST AND NTN NO. ON ALL OF YOUR SALES TAX INVOICE AS PER GOVT INSTRUCTION. 7. ENTRY OF CNG / LPG FITTED VEHICLES</p>	NO	2			

YOUR REF. NO.
DATE:

AUTHORIZED SIGNATURE



NATIONAL REFINERY LIMITED

7-B, Korangi Industrial Zone, Korangi, Karachi-74900, (Pakistan)
P.O.Box No. 8228
PABX: 5064981-86 Dir. 5060842 Fax No. (92-21) 5054679 & 5054663

NRL-FAF-LRU-001
Rev.: # 00
Dt.: 28-07-2003

Request For Quotation

Tel :
Fax :
Vendor No. 102518

Our Ref No. WHL-8020

No. 6000148675

Dated 30.10.2023

Please return this form duly completed and signed by authorized person in the sealed envelope. The due date for submission of tenders is

Due Date: 09.11.2023

PLEASE DROP YOUR QUOTATION IN BOX NO. 1

[Signature]
MANAGER LOCAL PURCHASE

Please quote your lowest prices for the following items. Your offer should remain valid for 45 DAYS. Please drop your quotation in above mentioned Box No. kept at NRL Reception Office. Please quote your GST No. and mention prices are inclusive or exclusive of GST. If not it will be assumed to be inclusive.

Delivery: Free delivery at our Ware House
Requirement: Within 7 days of our Purchase Order

* Collect Ex-Your Shop/Premises
 Immediate

Item	Material	Description	Unit	Quantity	Unit Pr.	Sales Tax	Total Amount Inclusive GST
		<p>ARE NOT ALLOWED INSIDE NRL PREMISES DUE TO SAFETY REQUIREMENT.THE SUPPLIERS ARE THEREFORE ADVISED TO DELIVER THE ORDERED MATERIALS THROUGH NON CNG/LPG FITTED VEHICLE</p> <p>8.THE VEHICLES DELIVERING GOODS MUST HAVE VALID FITNESS CERTIFICATE(IF APPLICABLE)VALID/ORIGINAL DRIVING LICENCE OF THE DRIVER & VALID/ORIGINAL CNIC OF OTHER STAFF OF THE SUPPLIER.NRL SAFETY & SECURITY PROCEDURES MUST BE STRICTLY FOLLOWED BY DRIVERS & ALL OTHER STAFF OF THE SUPPLIER</p> <p>9. QUOTATION ARE TO BE SUBMITTED PREFERABLY IS SEALED ENVELOP PROVIDED BY NRL ALONG WITH THIS RFQ HOWEVER IF SUPPLIERS ARE SUBMITTING OFFER IN THEIR OWN ENVELOPE,REFERENCE NO WITH DESCRIPTION OF MATERIAL AS MENTIONED IN OUR RFQ MUST BE MENTIONED ON THE ENVELOPE.</p> <p>10. QUOTATION RECEIVED ON FAX & E-MAIL WILL NOT BE CONSIDERED.</p> <p>11. QUOTATIONS MUST BE SIGNED BY AN AUTHORIZED REPRESENTATIVE AND MUST BE STAMPED WITH COMPANY STAMP.</p> <p>12. THE VEHICLES DELIVERING GOODS SHOULD BE EQUIPED WITH FIRE EXTINGUISHER.</p> <p>13. THE VEHICLES DELIVERING GOODS SHOULD HAVE SPARK ARRESTOR AT THE SILENCER.</p>					

YOUR REF. NO.
DATE:

AUTHORIZED SIGNATURE

COMPARISON BETWEEN GARRETT PD 500i & MZ 6100

GARRETT PD 500i		GARRETT MZ 6100	
STANDARD PROGRAMS	Over 20 application programs included.	STANDARD PROGRAMS	Over 15 application programs included.
SENSITIVITY	Up to 200 distinct sensitivity levels	SENSITIVITY	Up to 200 distinct sensitivity levels
ZONE INDICATIONS	33 independent zones	ZONE INDICATIONS	20 zones
MEETS IP55 STANDARDS	For moisture, foreign matter protection		
OVERHEAD CONTROL UNIT	All electronics-LCD, alarm light, LED bar graph, Control touch pads - integrated to eliminate wire exposure	OVERHEAD CONTROL UNIT	All electronics-LCD, alarm light, bar graph, Control touch pads - integrated to eliminate wire tempering
TAMPER PROOF SETTINGS	Three access levels of security clearance	TAMPER PROOF SETTINGS	Three levels of access control
SELF DIAGNOSTIC PROGRAM	complete and automatic	SELF DIAGNOSTIC PROGRAM	complete and automatic
ZONE SENSITIVITY BOOST	Adjustable in six areas	ZONE SENSITIVITY BOOST	20 Independently Adjustable boosts
BATTERY PACK (optional)	10-hours or 30-hours backup available	BATTERY PACK (optional)	1.5 amp-hour and 14 amp-hour lithium battery modules provide typical 1 hour or 10 hour operation times
WARRANTY	24 months, limited parts / labor	WARRANTY	24 months, limited parts / labor
PASSAGEWAY INTERIOR SIZE	width 30" (0.76 m) Height 80" (2.03 m) Depth 23" (0.58 m)	PASSAGEWAY INTERIOR SIZE	width 30" (0.76 m) Height 80" (2.03 m) Depth 23" (0.58 m)
OVERALL EXTERIOR SIZE	width 35" (0.90 m) Height 87" (2.21 m) Depth 23" (0.58 m)	OVERALL EXTERIOR SIZE	width 35" (0.90 m) Height 87" (2.21 m) Depth 23" (0.58 m)
SHIPPING SIZE	width 35.5" (0.90 m) Height 91.5" (2.32 m) Depth 6.25" (.16 m)	SHIPPING SIZE	width 35.5" (0.90 m) Height 91.5" (2.32 m) Depth 6.25" (.16 m)
SHIPPING WEIGHT	165 lbs. (74 kg)	SHIPPING WEIGHT	151 lbs. (68.5 kg)
TEMPERATURES	Operation -4 F (-20 C) to +122 F (50 C) . Humidity to 95% non-condensing. Storage 40 F (-40 C) to 158 F (70 C)	TEMPERATURES	Operation -4 F (-20 C) to +140 F (60 C) . Humidity to 95% non-condensing. Storage 40 F (-40 C) to 158 F (70 C)

POWER	Fully automatic 100 to 240 VAC, 50 or 60 Hertz, 45 watts no rewiring, switching or adjustments needed
REGULATORY INFORMATION	Meets TSA requirements for U.S airports, ECAC, STAC, AENA, CJAC and DFT for international airports. Meets Electrical safety and compatibility requirement for CE, FCC, CSA, IEC, ICNIRP and IEEE.
WEATHER PROOFING	Meets IP 55, IEC Standard. "Degrees of protection provided by enclosures." IEC 529. IP 65 optional
CONSTRUCTION	Attractive scratch and mar-resistant laminate. Detection heads and support heavy duty aluminum
CONTROL OUTPUTS	Solid state switches (low voltage AC or DC) for operating external alarms and control devices
REMOTE CONTROL (optional)	Desktop remote control with zone indication and/ or via network with CMA interface module
NETWORKING (optional)	Manage individual or groups of walkthroughs and perform statistical analysis of throughput
ALARM INDICATOR/ RANDOM ALARM FEATURE	33 Zones, volume-adjustable audible tone, bright LED visual and remote alarms. Random alarm feature; adjustable from 0 to 50 percent

POWER	Fully automatic 100 to 240 VAC, 50 or 60 Hertz, 40 watts no rewiring, switching or adjustments needed
REGULATORY INFORMATION	Meets electrical safety and compatibility requirements for CE, FCC, CSA, IEC, ICNIRP, IEEE additional certifications pending
WEATHER PROOFING	Meets IP 55, IP 65 (optional), IEC 529 standard for moisture, foreign matter protection
CONSTRUCTION	Attractive scratch and mar-resistant laminate. Detection heads and support heavy duty aluminum
CONTROL OUTPUTS (optional)	Module connector via RS 485 cable provides NO/NC relay contact
REMOTE CONTROL (optional)	Desktop remote control with zone indication and/ or via network with CMA interface module
NETWORKING (optional)	Manage individual or groups of walkthroughs and perform statistical analysis of throughput
RANDOM ALARM FEATURE	Adjustable from 0 to 100 percent